

# SOLAX CLOUD MONITORING



## Pocket Wi-Fi

### Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing designs
- Stable data transmission and good reliability
- Low profile and nice exterior

<b>Product Name</b>	Pocket Wi-fi
Model	Pocket Wifi 2.0
Supply Voltage	+3.3V
Frequency	2.400~2.472GHz
Antenna Gain	3dBi
Data upload intervals	5mins
Degree of protection	IP 65
Dimension	82*40*24.5mm
Net weight	34g

<b>Product Name</b>	Pocket LAN 2.0
Supply Voltage	+3.3 V
Data upload intervals	5min
Ethernet	10/100M
Net weight	54g
Dimension	123*29*42mm
Degree of protection	IP 65

## Pocket Lan



### Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing design
- Stable data transmission and good reliability
- Eco-green and modern design

<b>Product Name</b>	Pocket Wi-Fi Plus
Supply Voltage	+3.3V
Frequency	2.400~2.472GHz
Antenna Gain	3dBi
Data upload intervals	5mins
Degree of protection	IP 65
Dimension	108*42*28.8mm
Net weight	34g

## Pocket Wi-Fi Plus

### Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing designs
- Stable data transmission and good reliability
- Low profile and nice exterior
- Increase the external antenna, the signal is stronger

# METER & CT



## DDSU666

- Single-phase meter
- 80 A



## DTSU666

- Three-phase meter
- 80 A



## DDSU666-CT

- Single-phase meter
- 200 A
- With CT



## DTSU666-CT

- Three-phase meter
- 200 A
- With CT



## SDM230-Modbus

- Single-phase meter
- 100 A



## SDM630M-CT V2

- Three-phase meter
- 200 /600 /1500 A
- With CT



## ADAPTER BOX

Max. output voltage[V]	277
Max. output current[A]	5
Rated input voltage[V]	12
Degree of protection	IP65
Operating ambient temperature range [°C]	-25~60